



Product Specification Sheet

JP8 MIL-DTL-83133L

PROPERTY	UNIT		SPECIFICATION D1655	TEST METHOD	ITEM #
WORKMANSHIP					
Visual Rating	Rating		Clear and Bright	D4176	021
Saybolt Color	Number		Report	D156	010A
COMPOSITION					
Acidity, Total	mg KOH/g	max	0.10	D3242	100C
Aromatics	vol%	max	26.5	D6379	110A
Sulfur, Mercaptan	wt%	max	0.003	D3227	130
Sulfur, Total	wt%	max	0.30	D4294	150F
VOLATILITY					
Distillation temperature			--	D86	200A
Initial boiling	Celsius		Report	D86	201
10% recovered temperature	Celsius (Fahrenheit)	max	205 (401)	D86	202
20% recovered temperature	Celsius		Report	D86	213
50% recovered temperature	Celsius		Report	D86	204
90% recovered temperature	Celsius		Report	D86	206
Final boiling temperature	Celsius (Fahrenheit)	max	300 (572)	D86	211
Residue	%		1.5	D86	213
Loss	%		1.5	D86	214
Flash Point	Celsius (Fahrenheit)	max	38 (100)	D56	220B
Density at 15C	kg/m ³		775 - 840	D4052	
API gravity at 15C	API		Report	D4052	
Density at 60F	kg/m ³		Report	D4052	
API gravity at 60F	API		Report	D4052	231A
FLUIDITY					
Freeze point	Celsius (Fahrenheit)	max	-45.5 (-50) Jet A	D5972	300A
Freeze point	Celsius (Fahrenheit)	max	-47 (-53) Jet A-1	D5972	300A
Viscosity at -20C	mm ² /s		8	D7945	310
COMBUSTION					
Net Heat of Combustion	MJ/kg	min	42.8	D3338	400C
Hydrogen Content	wt%	min	13.4	D7171	
Smoke Point	mm	min	19.0	D1322	420
Naphthalenes	vol%	max	3.0	D1840	120
CORROSION					
Copper strip, 2 hr at 100C	Rating	max	1	D130	500
THERMAL STABILITY					
JFTOT - 2.5 hr @ 260 or 265				D3241	
Ellipsometric Tube rating	nm	max	80	D3241	600A
Filter pressure drop	mm Hg	max	25	D3241	601
CONTAMINANTS					
Existent gum	mg/100ml	max	7	D381/IP540	710
Microseperometer	Rating	min	85	D3948	750
ADDITIVES					
Fuel system icing inhibitor	vol %		0.07 - 0.10	D5006	830A
Electrical conductivity improver	pS/m		50 - 600	D2624	900
Electrical conductivity improver temperature			Report	D2624	901
Corrosion Inhibitor	mg/L		12 - 23	Calculated	QPL-25017

Notes ***If additives are present, limit is reduced to 70.
Product complies with ASTM D1655
All additives are injected at point of shipment per contract
Product complies with ASTM D1655. All additives are injected at point of shipment per contract